

GOLINE

“Plymovent GoLine: where protection against welding fume exposure starts.”



GOLINE AND GOLINE^{plus}

The GoLine and GoLine^{plus} of Plymovent is a range of welding fume extractors that provide effective protection against exposure to welding fume at workplaces where welding is less intensive.

The GoLine, is the entry level extractor for occasional welding applications as where the GoLine^{plus} is suitable for more industrial working environments.

WHY THE GOLINE AND GOLINE^{plus}

- Excellent price performance
- Effective protection against welding fume exposure
- NEN EN ISO 15012-1:2013/W3 compliant
- Suitable for steel and stainless steel welding applications

MOBILEGO AND MOBILEGO^{plus}

Compact and powerful mobile welding fume extractors fitted with an extraction arm up to three meter length. The arm can rotate 360° degree and is very easy to handle.

MONOGO AND MONOGO^{plus}

Single arm fume extractor with a reach up to four meter. The MonoGo is designed for fixed work places and can be mounted to a wall.



DUALGO AND DUALGO^{plus}

Dual arm fume extractor with a reach up to four meter. All DualGo models have a powerful fan, large filter and are designed to have both extraction arms in operation at the same time.

WHEN TO USE THE GOLINE, GOLINE^{plus} AND OTHER PLYMOVENT PRODUCTS

MobileGo and MonoGo are suitable for occasional welding applications	1 coil of solid welding wire or 7,5 kg of welding electrodes per month. TIG, due to low fume emission, is unrestricted.
DualGo and GoLine ^{plus} models are suitable for light and regular welding applications	2 coils of solid welding wire or 15 kg of welding electrodes per month.
MFD and SFD models are suitable for regular welding	1 coil of solid welding wire or 7,5 kg of welding electrodes per week.
MobilePro, the self cleaning mobile fume extractor is suitable for regular and intensive welding	Fluxed core welding applications, more than 1 coil of welding wire or 7,5 kg of welding electrodes per week.
MFS and SFS, the self cleaning fume extractors are suitable for regular and intensive welding	Fluxed core welding applications, more than 1 coil of welding wire or 7,5 kg of welding electrodes per week.

* DualGo has same filter as DualGo^{plus}



MOBILEGO

Perfect for flexible work places.



MONOGO

Ideal for fixed work station.



DUALGO

A real space saver!

TECHNICAL SPECIFICATIONS

	MobileGo	MobileGo ^{plus}	MonoGo	MonoGo ^{plus}	DualGo	DualGo ^{plus}
Power	1,1 kW		1,1 kW		2,2 kW	
Voltage	115V-1ph-50Hz 115V-1ph-60Hz 230V-1ph-50Hz		115V-1ph-50Hz 115V-1ph-60Hz 230V-1ph-50Hz		380V-3ph-50Hz 480V-3ph-60Hz 600V-3ph-60Hz	
Sound level	67 dB(A)		67 dB(A)		73 dB(A) <i>Inclusive silencer</i>	
Filter area main filter	15m ²	26m ²	15m ²	26m ²	26m ²	
Filtration steps	2 steps		2 steps		2 steps	
Efficiency ISO 15012-1	W3		W3		W3	
Service indicator	✓		✓		✓	
Extraction arm ø 160 mm	2 m EA arm 3 m EA arm	2 m KUA arm 3 m KUA arm	2 m EA arm 3 m EA arm 4 m EA arm	2 m KUA arm 3 m KUA arm 4 m KUA arm	2 + 2 m EA arm 2 + 3 m EA arm 2 + 4 m EA arm 3 + 3 m EA arm 3 + 4 m EA arm 4 + 4 m EA arm	2 + 2 m KUA arm 2 + 3 m KUA arm 2 + 4 m KUA arm 3 + 3 m KUA arm 3 + 4 m KUA arm 4 + 4 m KUA arm

EA arm: flexible exterior hose
KUA arm: aluminium tube

PLYMOVENT®
clean air at work

Plymovent Inc.

4090B Sladeview Cres. Unit 1
Mississauga, ON
L5L 5Y5 Canada

T +1 905 564 4748

F +1 905 564 4609

E ip@plymovent.com

*Plymovent cares about the air you breathe.
We offer products, systems and services which
ensure clean air at work, anywhere in the world.*

*We respect the environment and we deliver
high-quality products. Our expertise gained over
many years and our genuine commitment to
customer requirements enable us to provide
precisely the solutions you need.*