

REN NOZZLE

REN NOZZLE

The REN Nozzle is highly suitable for Plymovent fixed extractors and exhaust reels. The REN is designed to take in ambient cooling air, thereby reducing the exhaust emission temperature. Constructed with molded, high-temperature resistant rubber.

APPLICATIONS

The CP Rubber Hose with Wire is intended to be used for the following applications:



- To eliminate hazardous diesel and CNG exhaust emissions with our vehicle exhaust source capture and removal systems for the following segments: auto and light-duty trucks.

SPECIFICATIONS

■ Physical dimensions and properties	
Material • nozzle	EPDM molded rubber material with no internal wire helix
Color	black
Hose diameters	<ul style="list-style-type: none"> 3" (75mm) 4" (100mm) 5" (125mm) 6" (150mm)
■ Ambient conditions	
Operating temperature:	
• min.	• °F (0°C)
• max.	• 600°F (315°C)
■ Options and accessories	
Hook and chain are a standard with optional suction cup available.	
■ Product combinations	
<ul style="list-style-type: none"> Hose Reels Rail Systems Booms Extractor 	<ul style="list-style-type: none"> SER, MHR, MER MRP, STR FE, FEF, FEB Light & Heavy Dute FumeCaddie
■ Scope of supply	
• Order information	See remaining specifications
• Number/package	1
■ Features & benefits	
<ul style="list-style-type: none"> Loose fit over the tailpipe Hook and chain to connect 	

<ul style="list-style-type: none"> Works with flush-mounted setups The oval adapter can work on dual exhaust pipes Bell nozzle can work on wide or twin pipes 	
■ Physical dimensions and properties	
Gross weight	
Packing dimensions	
Harmonized Tariff Code	
Country of origin	

Product type	REN Nozzle
Article no.	<ul style="list-style-type: none"> 00000007589 00000007520 00000007521 00000007522 00000007523
Product category	nozzle
Version	20220324/0
	<ul style="list-style-type: none"> RECH 40 NOZZLE - CP RECH 45 NOZZLE - CP REN-OVAL NOZZLE- CP REN-WIDE OVAL NOZZLE-CP REN-WIDE OVAL NOZZLE-SUC-CP

Always check the latest version on www.plymovent.com

