PLYM SVENT<sup>®</sup> clean air at work

# **TRUCK EXTRACTION NOZZLE**

### TEN

The Truck Extraction Nozzle (TEN) is an adjustable nozzle which can connect to tailpipes that are hard to reach and/or have an irregular shape. The flexibility of the TEN accommodates an touchless interface between the nozzle and the exhaust.

The detachable magnetic hose coupling positioner allows the operator to position the hose on any desired magnetic surface.

The TEN facilitates European standard EURO 6 and American EPA 07 tailpipes.



#### APPLICATIONS

The TEN is intended to be used for the following applications:



• To eliminate hazardous vehicle exhaust emissions with our vehicle exhaust capture and removal systems for the following segments: fire and emergency service stations as well as military facilities.

#### SPECIFICATIONS

Physical dimensions and properties	
Material • nozzle	<ul> <li>powdercoated aluminium</li> </ul>
<ul><li>positioner</li></ul>	<ul> <li>powdercoated steel</li> </ul>
Colour	black/yellow
Hose diameter	150 mm (6 in.)
Airflow	
Recommended airflow car	500 m <sup>3</sup> /h (295 cfm)
Recommended airflow truck	1000 m³/h (588 cfm)
Ambient conditions	
Temperature range	depends on hose up to 400°C (752°F)
Max. relative humidity	80%
Outdoor use allowed	no
Product combinations	
Compatible with the EH, ES or EF hose	
Scope of supply	
The TEN (hose to be ordered seperately)	
Order information	
Article no.	0000111744
Number/package	1
Shipping data	
Gross weight	19 kg (42 lbs)
Packing dimensions	800 x 1200 x 1500 mm (31 x 47 x 59 in.)
Harmonized Tariff Code	84219990

## FEATURES

- 360° flexibility with the designed ball and socket joint
- Easy locking mechanism with quarter turn locking handle
- Rotating wheels with brakes
- Removable magnetic hose coupling positioner for 150 mm (6 in.) hose
- Compatible with all Plymovent exhaust hoses



#### DIMENSIONS



**PLYMFJVENT**<sup>®</sup> clean air at work



Product type Article no. Product category Version Truck Extraction Nozzle 0000111744 nozzles 020919/0

Always check the latest version on www.plymovent.com